

FAA-A

Sky Air series Wall mounted unit

High capacity wall mounted units for small commercial applications



FAA-A pair combinations

Indoor unit	Outdoor unit	Cooling capacity kW	Heating capacity kW	Seasonal efficiency (according to EN14825)								Prices		
				Cooling				Heating (Average climate)				Indoor unit €	Outdoor unit €	Set price €
				Energy label	Pdesign kW	SEER	A.E.C. kWh	Energy label	Pdesign kW	SCOP	A.E.C. kWh			

Sky Air Alpha series combinations

SkyAir Alpha-series

1-phase (230V)	FAA71A	RZAG71MV1	6,8	7,5	A++	6,8	6,58	362	A+	4,7	4,02	1637	1.084,-	2.261,-	3.345,-
	FAA100A	RZAG100MV1	9,5	10,8	A++	9,5	6,42	518	A+	7,8	4,01	2723	1.132,-	2.837,-	3.969,-
3-phase (400V)	FAA71A	RZAG71MY1	6,8	7,5	A++	6,8	7,03	362	A+	4,7	4,02	1637	1.084,-	2.330,-	3.414,-
	FAA100A	RZAG100MY1	9,5	10,8	A++	9,5	6,42	518	A+	7,8	4,01	2723	1.132,-	2.868,-	4.000,-

Sky Air Advance series combinations

SkyAir Advance-series

1-phase (230V)	FAA71A	RZASG71MV1	6,8	7,5	A++	6,8	6,41	371	A	4,5	3,9	1615	1.084,-	1.836,-	2.920,-
	FAA100A	RZASG100MV1	9,5	10,8	A+	9,5	5,83	570	A+	6,0	3,85	2182	1.132,-	2.305,-	3.437,-
3-phase (400V)	FAA100A	RZASG100MY1	9,5	10,8	A+	9,5	5,83	570	A+	6,0	3,85	2182	1.132,-	2.374,-	3.506,-

Sky Air Active combinations

SkyAir Active-series

1-phase (230V)	SB.FAA71/AZAS71V	6,8	7,5	A+	6,8	5,77	412	A	4,5	3,81	1654	-	-	2.242,-
	SB.FAA100/AZAS100V	9,5	10,8	A	9,5	5,25	633	A	6,0	3,81	2205	-	-	2.607,-
3-phase (400V)	SB.FAA100/AZAS100Y	9,5	10,8	A	9,5	5,25	633	A	6,0	3,81	2205	-	-	2.643,-

Remote controller is not included in Indoor unit price and Set price and has to be ordered separately.

Accessories for FAA-A units

Material name	Description	Price €
BRC7EB518	Infra-red wireless remote controller	221,-
BRC1E53A	Standard wired remote controller with full-text interface and back-light with new energy saving, sound minimization & duty rotation functions for Austria	143,-
BRC1E53B	Standard wired remote controller with full-text interface and back-light with new energy saving, sound minimization & duty rotation functions for Czech, Croatia, Hungarian, Romanian, Slovenian, Bulgarian	143,-
BRC1E53C	Standard wired remote controller with full-text interface and back-light with new energy saving, sound minimization & duty rotation functions for Slovakian and Albanian	143,-
BRC1H51W/S/K	New premium wired remote controller with white/silver/black color - will fully replace BRC1E53* after stock out.	164,-
K-KDU572EVE	External drain pump kit (1000 mm delivery height)	654,-
BRP069A81	Sky Air WLAN adaptor for WiFi App control	132,-

Indoor unit		FAA	71A	100A
Dimensions	Unit	HeightxWidthxDepth	mm	290x1.050x238
Weight	Unit		kg	13
Fan - Air flow rate	Cooling	High/Low	m ³ /min	18/14
	Heating	High/Low	m ³ /min	18/14
Sound power level	Cooling		dBA	61
	Heating		dBA	61
Sound pressure level	Cooling	High/Low	dBA	45/40
	Heating	High/Low	dBA	45/40
Refrigerant	Type			R-32 / R-410A
Control system	Infrared remote control			BRC7EB518
	Wired remote control			BRC1E53A/B/C or BRC1H51W/S/K
Power supply	Phase / Frequency / Voltage	Hz / V		1~ / 50 / 220-240

(1) With wired R/C; (2) With wireless R/C; (3) With Sky Air Alpha series

See page 53 for technical data of the RZAG outdoor units, page 54 for technical data of the RZASG outdoor units and page 55 for technical data of the AZAS outdoor units.